

HZS50 CONCRETE BATCHING PLANT

GENERAL

• MODEL: HZS50

CAPACITY: MAX 50M3/H

NUMBER OF AGRREGATE: 3—5
 MAX.AGRREGATE SIZE: 60mm

• DISCHARGE HEIGHT: 3.8m

SAND MATERIAL RANGE: 0—300kg/±2%

• AGGREGATE MATERIAL RANGE: 0—2000kg/±2%

CEMENT MATERIAL RANGE: 0—500kg/±2%
 WATER MATERIAL RANGE: 0---200kg/±2%
 ADDITIVE MATERIAL RANGE: 0---50kg/±2%

TYPE: STATIONARY

 MODE OF OPERATION: AUTOMATIC/ MANUAL FULLY COMPUTER CONTROL SYSTEM IN ENGLISH

ELECTRIC POWER SOURCE: 380V/50Hz FOR DRIVING,230V/50Hz CONTROL

TOTAL POWER: 120KW

MAIN COMPONENTS

COLD BIN

• CAPACITY: 6 m3

QUANTITY: 4 PCS

VIBRATOR: 0.25KW x 2PCS x 1SET ONLY FOR FINE AGGREGATE

• BIN SIZE (Lx W): 2800mm x 2200mm

LOADING HEIGHT: 2700mm

WINDLASS

CAPACITY: 1600L/BATCH

• MOTOR: 18.5KW

MIXER

TYPE: HORIZONTAL TWIN SHAFT MIXER

CAPACITY: 50M3/H

MODEL:SICOMA MEO SERIES

• MOTOR: 18.5kw x 2PC +SHAFT-MOUNTED REDUCER

• MOTOR OF LUBRICATE OIL PUMP: 0.25KW

DISCHARGE GATE CYLINDER POWER: 1.2KW



COLLECT AND DISCHARGE MATERIAL SYSTEM

AGGREGATE TEMPORARILY STORAGE: 1.6M3

WEIGHING SENSOR RANGE: 2000kgDIAMETER OF BUTTERFLY VALVE: 300mm

VIBRATING MOTOR POWER: 0.15kw CEMENT SUPPLY AND WEIGHING SYSTEM

VOLUME OF CEMENT WEIGHING FILLER: 0.35M3

WEIGHING SENSOR RANGE: 500kg

DIAMETER OF BUTTERFLY VALVE: 300mm

VIBRATING MOTOR POWER: 0.15kw

WATER SUPPLY AND WEIGHING SYSTEM

VOLUME OF WATER WEIGHING FILLER: 0.3 M3

WEIGHING SENSOR RANGE: 200kg

• DIAMETER OF BUTTERFLY VALVE: 100mm

WATER PUMP MOTOR:3kw

ADDITIVE SUPPLY AND WEIGHING SYSTEM

VOLUME OF ADDITIVE WEIGHING FILLER: 0.02 M3

WEIGHING SENSOR RANGE: 50kg

DIAMETER OF BUTTERFLY VALVE: 50mm

PUMP MOTOR:1.1kw

AIR COMPRESSOR

TYPE: AIR COOLING TYPE

ADJUSTABLE PRESSURE: 0—5KG/CM2

MOTOR: 7.5 KWCAPACITY: 1 M3

INCLUDE AIR TANK AND VALVE AND PIPE

RATED PRESSURE: 0.7 --- 1.2 MPa

CONTROL SYSTEM

RANGE OF OPERATING TEMPERATURE: 0—55 °C

RANGE OF OPERATING HUMIDITY: 30%---85%

PLC: ADOPT INTERNATIONAL FAMOUS COMPANY PLC

CONTROL DISTRIBUTOR: ADOPT INTERNATIONAL FAMOUS COMPANY

CABIN: COLOR STEEL PLATE MADE WITH AIR CONDITIONER

CABLE: ACCORDING TO STANDARD

CONTROL DESK: COMPUTER CONTROL, WEIGHING STEM, BUTTON AND INDICATOR

CEMENT SCREW CONVEYER

TYPE: SCREWCAPACITY: 60T/H

MOTOR: 7.5KW GEAR MOTOR

QUANTITY: 2 UNITS









